

US011867059B2

(12) **United States Patent**
Staack et al.

(10) **Patent No.: US 11,867,059 B2**
(45) **Date of Patent: Jan. 9, 2024**

(54) **SYSTEMS AND METHODS FOR FORMING A SUBTERRANEAN BOREHOLE**

E21B 10/42 (2006.01)
E21B 41/00 (2006.01)

(71) Applicant: **The Texas A&M University System**,
College Station, TX (US)

(52) **U.S. Cl.**
CPC *E21B 7/15* (2013.01); *E21B 4/02*
(2013.01); *E21B 10/42* (2013.01); *E21B*
41/0085 (2013.01)

(72) Inventors: **David Staack**, College Station, TX
(US); **Li-Jung Tai**, Bryan, TX (US);
Dion S. Antao, College Station, TX
(US); **Xin Tang**, College Station, TX
(US)

(58) **Field of Classification Search**
CPC E21B 7/15
See application file for complete search history.

(73) Assignee: **The Texas A&M University System**,
College Station, TX (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 245 days.

3,679,007 A 7/1972 O'Hare
5,106,164 A 4/1992 Kitzing et al.
5,738,178 A * 4/1998 Williams E21B 4/02
175/73

(21) Appl. No.: **17/288,648**

7,270,195 B2 9/2007 MacGregor et al.
7,416,032 B2 8/2008 Moeny et al.
8,746,265 B2 6/2014 Nilsson et al.
9,822,588 B2 11/2017 Kocis
2006/0037779 A1 2/2006 Moeny et al.

(22) PCT Filed: **Oct. 30, 2019**

(86) PCT No.: **PCT/US2019/058859**

(Continued)

§ 371 (c)(1),
(2) Date: **Apr. 26, 2021**

OTHER PUBLICATIONS

(87) PCT Pub. No.: **WO2020/092559**

PCT/US2019/058859 International Search Report and Written Opin-
ion dated Mar. 19, 2020 (12 p.).

PCT Pub. Date: **May 7, 2020**

(Continued)

(65) **Prior Publication Data**
US 2021/0396079 A1 Dec. 23, 2021

Primary Examiner — Giovanna Wright
(74) *Attorney, Agent, or Firm* — Conley Rose, P.C.

Related U.S. Application Data


(57) **ABSTRACT**

(60) Provisional application No. 62/752,407, filed on Oct.
30, 2018.

Systems and methods for drilling a borehole are disclosed.
In an embodiment, the system includes a drill bit and a
plasma inducing apparatus coupled to the drill bit. The
plasma inducing apparatus is configured to generate plasma.

(51) **Int. Cl.**
E21B 7/15 (2006.01)
E21B 4/02 (2006.01)

20 Claims, 7 Drawing Sheets



References Cited

2009/0133929	A1	5/2009	Rodland	
2013/0277116	A1	10/2013	Knüll et al.	
2014/0008968	A1	1/2014	Moeny	
2014/0209308	A1 *	7/2014	Baldasaro C04B 40/0003 166/293
2015/0167439	A1	6/2015	Kasevich et al.	
2016/0017663	A1 *	1/2016	Moeny E21B 17/003 175/327
2017/0058608	A1	3/2017	Fraser et al.	
2017/0067292	A1	3/2017	Bayol et al.	
2017/0204669	A1	7/2017	Lehr et al.	
2017/0350206	A1	12/2017	Kocis et al.	
2018/0209217	A1	7/2018	Moeny et al.	

European Patent Application No. 19880290.2 extended European search report dated May 11, 2022 (9 pages).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7

1

SYSTEMS AND METHODS FOR FORMING A
SUBTERRANEAN BOREHOLECROSS-REFERENCE TO RELATED
APPLICATIONS

This application is a 35 U.S.C. § 371 national stage application of PCT/US2019/058859 dated Oct. 30, 2019, and entitled “Systems and Methods for Forming a Subterranean Borehole,” which claims benefit of U.S. provisional patent application Ser. No. 62/752,407 filed Oct. 30, 2018, and entitled “Drill Head and Drilling Method Using Targeted Energy Focusing to Induce Micro-Cracking,” each of which is hereby incorporated herein by reference in its entirety for all purposes.

STATEMENT REGARDING FEDERALLY
SPONSORED RESEARCH OR DEVELOPMENT

This invention was made with government support under DE-EE0008605 awarded by the Department of Energy. The government has certain rights in the invention.

BACKGROUND

Holes or bores (e.g., such as wellbores, or other boreholes) may be formed or extended in a subterranean formation by engaging a drill bit with the formation. The cost of drilling a borehole may be very high and is proportional to the length of time it takes to drill to the desired depth and location. The time required to drill the borehole, in turn, is greatly influenced by the rate at which the drill bit can drill the borehole through the subterranean formation, which may be referred to herein as the “rate of penetration” (ROP).

BRIEF SUMMARY

Some embodiments disclosed herein are directed to a system for drilling a borehole. In an embodiment, the system includes a tubular string, and a drill bit coupled to the tubular string. In addition, the system includes a plasma inducing apparatus coupled to the drill bit, and a power conversion assembly coupled to the tubular string. The plasma inducing apparatus is configured to generate plasma from electric current generated within the power conversion assembly.

In other embodiments the system includes a tubular string, and a bottom hole assembly coupled to the tubular string. The bottom hole assembly includes a downhole motor, a power conversion assembly configured to generate electric current from operation of the downhole motor, a drill bit, and an electrode assembly coupled to a downhole end of the drill bit. The electrode assembly is configured to generate plasma when energized with electric current from the power conversion assembly.

Other embodiments disclosed herein are directed to a method of drilling a borehole. In an embodiment, the method includes: (a) rotating a drill bit about a central axis; (b) engaging the drill bit with a subterranean formation during (a); (c) generating electric current downhole; (d) generating plasma from a plasma inducing apparatus coupled to the drill bit during (b) using the electric current generated in (c); (e) weakening the subterranean formation with the plasma during (d); and (f) extending the borehole within a subterranean formation as a result of (a)-(e).

Embodiments described herein comprise a combination of features and characteristics intended to address various shortcomings associated with certain prior devices, systems,

2

and methods. The foregoing has outlined rather broadly the features and technical characteristics of the disclosed embodiments in order that the detailed description that follows may be better understood. The various characteristics and features described above, as well as others, will be readily apparent to those skilled in the art upon reading the following detailed description, and by referring to the accompanying drawings. It should be appreciated that the conception and the specific embodiments disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes as the disclosed embodiments. It should also be realized that such equivalent constructions do not depart from the spirit and scope of the principles disclosed herein.

BRIEF DESCRIPTION OF THE DRAWINGS

For a detailed description of various exemplary embodiments, reference will now be made to the accompanying drawings in which:

FIG. 1 is a schematic view of a system for drilling a borehole in a subterranean formation according to some embodiments;

FIG. 2 is a schematic, partial side cross-sectional view of the bottom hole assembly of the system of FIG. 1 according to some embodiments;

FIG. 3 is an enlarged schematic view of the power distribution assembly and drill bit of the system of FIG. 1 according to some embodiments;

FIG. 4 is a perspective view of a drill bit for use within the system of FIG. 1 according to some embodiments;

FIG. 5 is a bottom end view of the drill bit of FIG. 4;

FIG. 6 is a cross-sectional side view of the drill bit of FIG. 4; and

FIG. 7 is a flow chart illustrating a method of drilling a borehole in a subterranean formation according to some embodiments.

DETAILED DESCRIPTION

The following discussion is directed to various exemplary embodiments. However, one skilled in the art will understand that the examples disclosed herein have broad application, and that the discussion of any embodiment is meant only to be exemplary of that embodiment, and not intended to suggest that the scope of the disclosure, including the claims, is limited to that embodiment.

Certain terms are used throughout the following description and claims to refer to particular features or components. As one skilled in the art will appreciate, different persons may refer to the same feature or component by different names. This document does not intend to distinguish between components or features that differ in name but not function. The drawing figures are not necessarily to scale. Certain features and components herein may be shown exaggerated in scale or in somewhat schematic form and some details of conventional elements may not be shown in interest of clarity and conciseness.

In the following discussion and in the claims, the terms “including” and “comprising” are used in an open-ended fashion, and thus should be interpreted to mean “including, but not limited to” Also, the term “couple” or “couples” is intended to mean either an indirect or direct connection. Thus, if a first device couples to a second device, that connection may be through a direct connection, or through an indirect connection via other devices, components, and connections. In addition, as used herein, the terms “axial”

3

and “axially” generally mean along or parallel to a central axis (e.g., central axis of a body or a port), while the terms “radial” and “radially” generally mean perpendicular to the central axis. For instance, an axial distance refers to a distance measured along or parallel to the central axis, and a radial distance means a distance measured perpendicular to the central axis. Any reference to up or down in the description and the claims will be made for purposes of clarity, with “up”, “upper”, “upwardly” “upstream”, “uphole” meaning toward the surface of the borehole and with “down”, “lower”, “downwardly” “downstream” or “downhole” meaning toward the terminal end of the borehole, regardless of the borehole orientation. As used herein, the terms “approximately,” “about,” “substantially,” and the like mean within 10% (i.e., plus or minus 10%) of the recited value. Thus, for example, a recited angle of “about 80 degrees” refers to an angle ranging from 72 degrees to 88 degrees. As used herein, the term “elongate” when used to refer to a body, means that the longitudinal or axial length of the body is longer than its lateral or radial width.

As previously described, the cost of drilling or forming a subterranean borehole may be directly related to the ROP of the drill bit forming the borehole. Thus, it is generally desirable to increase the ROP of a borehole drilling operation so as to reduce the costs associated therewith. A given drill bit may have a higher ROP for formations that are weaker or that present less resistance to shearing, puncturing, etc. as a result of engagement of the drill bit. Thus, it may be desirable to weaken the subterranean formation prior to or simultaneously with engaging the formation with the drill bit so as to increase the ROP during a drilling operation. Accordingly, examples disclosed herein include drill bits and associated drilling systems or assemblies that include electrode assemblies that are configured to weaken a subterranean formation that is to be engaged by the drill bit and thereby increase the ROP during a drilling operation.

In the specific embodiments disclosed herein, drill bits are described for drilling or forming a borehole in a subterranean formation for accessing hydrocarbons (e.g., oil, gas, condensate, etc.). However, it should be appreciated that the drill bits and associated systems described herein may be employed within any system for forming a subterranean borehole, regardless of the purpose of such a borehole formation. For instance, in some embodiments, the disclosed drill bits (and/or the associated drilling systems) may be utilized to form a subterranean borehole for accessing other resources (e.g., such as ground water), or to form a pathway through a subterranean formation for conduits, cables, fluids, and/or other mechanisms or substances. Further, in some embodiments, embodiments of the disclosed drill bits and/or drilling systems may be utilized to form bores or holes in other mediums (that is, other than a subterranean formation). For instance, in some embodiment, embodiments of the disclosed drill bits may be utilized to drill holes in teeth (e.g., such as for dental applications), walls, structures, etc. Thus, any specific reference to the forming of boreholes for accessing subterranean hydrocarbon resources is merely meant to provide one example implantation of the disclosed embodiments, and should not be interpreted as limiting all potential uses thereof.

Referring now to FIG. 1, a schematic view of an embodiment of a system 10 for drilling a borehole 3 in a subterranean formation 7 is shown. In general, system 10 includes surface equipment 12, a tubular drill string 16, and a bottom-hole assembly (BHA) 100.

In this example, drill string 16 includes a plurality of elongate pipe joints connected together end-to-end. In some

4

embodiments, the elongate pipe joints may be threadably coupled to one another; however, any suitable coupling mechanism or method may be used to join the elongate pipe joints in various embodiments. The drill string 16 may be supported by and extended from the surface equipment 12 into borehole 3. During operations, drill string 12 may both support the BHA 100 within borehole 3 and provide a flow path for fluids, such as, for instance, drilling mud, into the borehole 3 during drilling operations. In some embodiments, drill string 16 may comprise any other suitable tether (e.g., such as wireline, slickline, e-line, coiled tubing, etc.) for supporting BHA 100 within borehole 3 that may or may not also comprise or define a fluid flow path therethrough.

The BHA 100 is coupled to a distal or downhole end of the drill string 16 within borehole 3. In this embodiment, BHA 100 includes a central or longitudinal axis 115, a downhole motor 110, a power conversion assembly 120, and a drill bit 150. Generally speaking, the power conversion assembly 120 is axially positioned between the downhole motor 110 and drill bit 150.

During drilling operations, drill bit 150 is rotated with weight-on-bit (WOB) applied to drill the borehole 3 through the earthen formation 7. In this embodiment, drill bit 150 is rotated by the downhole motor 110. In other embodiments, surface equipment 12 may include additional components for rotating tubular string 16 and drill bit 150 (e.g., such as a rotary table, top drill, power swivel, etc.). In still other embodiments, the drill bit 150 may be rotated by a combination of the downhole motor 110 and additional, surface-mounted components (e.g., such as those noted above).

Referring still to FIG. 1, while drilling borehole 3, a suitable drilling fluid is pumped under pressure from the surface 5 through the drill string 16. The drilling fluid flows down drill string 16, through the BHA 100, and is ultimately discharged at the bottom of borehole 3 through nozzles (not shown) in face of drill bit 150 (described in more detail below). Thereafter, the drilling fluid circulates uphole to the surface 5 through an annular space or annulus 9 radially positioned between tubular string 16 and the sidewall of borehole 3.

Further, during these operations and as will be described in more detail below, power conversion assembly 120 generates electric current, which is utilized to selectively generate plasma at one or more electrode assemblies 160 disposed on the face of drill bit 150. The plasma creates cracks and fractures within the formation 7 proximal drill bit 150 so as to weaken the formation 7, thereby offering the potential to increase the ROP of the drilling operation. Additional details of these operations as well as embodiments of the BHA 100 are discussed in more detail below.

Referring now to FIG. 2, in some embodiments downhole motor 110 may comprise progressive cavity or positive displacement motor that is driven via the flow of pressurized drilling fluid therethrough. In particular, the downhole motor 110 includes a rotor 114 rotatably disposed within a stator 112. The rotor 114 includes a shaft formed with one or more helical vanes or lobes extending along its length. In addition, the stator 112 is formed of an elastomer liner bonded to the inner wall of the stator housing that defines helical lobes complementary to that of the lobe or lobes of the rotor 114. During operations, pressurized drilling fluid is flowed between the rotor 114 and stator 112, thereby driving rotor 114 to rotate within the stator 112 in an eccentric manner. More particularly, the rotor 114 generally orbits about the central longitudinal axis of the stator 112, which is coaxially aligned with central axis 115, while simultaneously rotating about a central axis (not shown) of the rotor 112.

5

A driveshaft assembly **116** is coupled between a downhole end of rotor **114** and the drill bit **150**. Drive shaft assembly **116** includes one or more shafts, joints (e.g., universal joints), connectors (not shown), or combinations thereof that transfer torque from the rotor **114** to drill bit **150**. Thus, driveshaft assembly **116** converts the precessional or orbital motion of the rotor **114** into rotation of drill bit **150** about central axis **115**. In addition, while not specifically shown, it should be appreciated that driveshaft assembly **116** may also include one or more bearing assemblies for reducing friction and generally supporting the rotational motion of driveshaft assembly **116** and drill bit **150** during drilling operations.

It should be appreciated that the design of downhole motor **110** may be varied in other embodiments. For instance, in some embodiments downhole motor **110** may be configured to rotate rotor **114** concentrically about axis **115** (e.g., rather than precessionally or eccentrically as previously described above). Accordingly, the design of driveshaft assembly **116** may also be varied so as to correspond with the design and arrangement of downhole motor **110** during drilling operations.

Referring still to FIG. 2, as previously described above, power conversion assembly **120** is axially disposed between downhole motor **110** and drill bit **150** within BHA **100**. The components of power generation assembly **120** may be generally disposed circumferentially about driveshaft assembly **116**. In addition, while not specifically shown, a fluid flow path may be defined through driveshaft assembly **116** and/or between driveshaft assembly **116** and the power conversion assembly **120** to communicate drilling fluid flowing through the downhole motor **110** to the drill bit **150**, where it is then emitted from one or more nozzles (not shown) in the drill bit **150**.

Generally speaking, power conversion assembly **120** generates electric current from the rotation of rotor **114** within downhole motor **110**, and then supplies that electric current to the drill bit **150** so as to selectively generate plasma (or “plasmatic discharges”) from the electrode assemblies **160** during drilling operations. In addition, as will be described in more detail below, power conversion assembly **120** may also multiply or increase a voltage of the generated electric current, so as to achieve a desired power discharge via the electrode assemblies **160**. In this embodiment, power conversion assembly **120** includes an alternator **122**, a power storage assembly **124**, an inverter **128**, a transformer **130**, a voltage multiplier and rectifier **132**, and a power distribution assembly **134**.

Alternator **122** generates a flow of electric current utilizing the rotational motion of the rotor **114** and/or driveshaft assembly **116** during drilling operations. In particular, in some embodiments, alternator **122** includes a rotor **123** that is rotatably coupled to driveshaft assembly **116** so that as driveshaft assembly **116** is rotated about central axis **115**, rotor **123** is also rotated about the central axis **115**. Alternator **122** also includes one or more coils **121** wound circumferentially about the rotor **123**. During drilling operations, as the driveshaft assembly **116** rotates about the central axis **115** (e.g., via the orbiting motion of rotor **114** within downhole motor **110** as previously describe above), the rotor **123** rotates within the coils **121**, which thereby generate a magnetic field that in turn induces an electric current flow within the coils **121**.

Power storage assembly **124** is disposed downhole of alternator **122** and stores electric power generated by alternator **122**. In particular, power storage assembly **124** includes a plurality power storage devices **126** (e.g., batteries, capacitors, etc.), electrically coupled to one another and

6

to the coils **121** within alternator **122**. In this embodiment, the power storage devices **126** are batteries (e.g., 12 Volt batteries, 48 Volt batteries, etc.). Thus, power storage devices **126** may also be referred to herein as “batteries **126**.” The batteries **126** may be coupled to one another in series (e.g., such that a positive terminal of each battery **126** is electrically coupled to a negative terminal of another of the batteries **126**), or in parallel (e.g., such that all of the positive terminals of batteries **126** are coupled to one another and all of the negative terminals of batteries **126** are coupled to one another). The choice between series connection or parallel connection between the batteries **126** may be driven by a desired output voltage from the power storage assembly **124** to the other components within power conversion assembly **120**, the power storage capacity of the batteries **126**, etc.

In this embodiment, the batteries **126** within power storage assembly **124** are elongate cylindrical bodies that are parallel to and radially offset from central axis **115**. More specifically, the batteries **126** are uniformly circumferentially spaced about central axis **115** and driveshaft assembly **116**. However, it should be appreciated that batteries **126** may have alternative shapes or forms, and/or the batteries **126** may have alternative arrangements or orientations within the power conversion assembly **124** in other embodiments.

Referring still to FIG. 2, inverter **128** is positioned downhole of and electrically coupled to the power storage assembly **124**. Thus, during drilling operations, electric current flows from batteries **126** of power storage assembly **124** to inverter **128**. The electric current produced from batteries **126** may be direct current (DC). Generally speaking, during operations, inverter **128** converts the DC current provided from batteries **126** to alternating current (AC). In general, inverter **128** may comprise any suitable circuit(s) and/or other mechanisms for affecting the conversion of DC current to AC current.

Transformer **130** is positioned downhole of inverter **128** and increases the voltage of the AC current emitted from inverter **128** to a higher, desired voltage. In some embodiments, the transformer **130** may receive an input current (e.g., from inverter **128**) having a voltage of about 12 to 400 V (AC) and may produce an output current having a voltage of about 1 kV (AC) to about 50 kV (AC). In some specific embodiments, the transformer **130** may receive an input current having a voltage of about 12 V (AC) and produce an output current having a voltage of about 3 kV (AC), or may receive an input current having a voltage of about 120 V (AC) and produce an output current having a voltage of about 10 kV (AC). While not specifically shown, it should be appreciated that transformer **130** may, in some embodiments, comprise one or more coils or windings that create a varying magnetic field when energized with an electric current (e.g., such as an electric current supplied from inverter **128**), so as to induce an output electric current (e.g., an output AC electric current) at a different (e.g., in this case higher) voltage than the input electric current.

Voltage multiplier and rectifier **132** is disposed downhole of and electrically coupled to transformer **130**. Thus, during drilling operations, the AC electric current output from transformer **130** is supplied to voltage multiple and rectifier **132**. In some embodiments, the voltage multiplier and rectifier **132** may comprise a Cockcroft-Walton generator, and thus, may be generally referred to herein as a “generator **132**.” During drilling operations, generator **132** generates a high voltage DC current based on the AC current received from transformer **130**. In addition to effectively converting

the AC electric current from transformer **130** into DC current, the DC current output from generator **132** also has a higher voltage than the input AC current supplied from transformer **130**. In some embodiments, the DC current output from generator **132** has a voltage potential of approximately 10 kV or greater (e.g., approximately 50 kV). In addition, in some embodiments, the DC current output from generator **132** has a current of approximately 10 mA (however, currents above and below 10 mA are also contemplated herein).

The relatively high output DC electric current from the generator **132** is then supplied to the power distributor **134**. Power distributor **134** may comprise one or more circuits, controllers, and/or other devices that selectively emit the output electric current from generator **132** to the electrode assemblies **160** coupled to drill bit **150**. In particular, in some embodiments, power distributor **134** provides electric current to the electrode assemblies **160** in a desired sequential order or pattern. In some embodiments, the sequence or sequential order for providing electric current to the various electrode assemblies **160** is tailored and configured to weaken a portion or surface of the formation **7** prior to (or simultaneous with) engaging that surface or portion of the formation **7** with the drill bit **150**. In some embodiments, the speed in which the energization sequence for the electrode assemblies **160** is carried out may be dictated or based on a rotational speed of the drill bit **150** (e.g., about axis **115**) during drilling operations.

In at least some embodiments, power distributor **134** rapidly transfers or applies a relatively high voltage electric current to the electrode assemblies **160**. For instance, in some embodiments, the power distributor **134** transfers or applies about 10 volts per nanosecond (V/ns) or greater to the electrode assemblies **160** during drilling operations. In some embodiments, the power distributor **134** transfers or applies greater than or equal to about 500 V/ns to the electrode assemblies **160** during drilling operations. Without being limited to this or any other theory, a relatively rapid transfer of higher voltage electric current to the electrode assemblies **160** may allow for relatively low energy, high voltage pulses to be generated within the liquids filling the borehole **3**, regardless of the conductivity of the liquids.

Referring now to FIGS. **2** and **3**, in some embodiments, power distributor **134** includes a plurality of electrical contacts **138a**, **138b** that are coupled to the electrode assemblies **160** within drill bit **150**. In particular, in the embodiment shown in FIG. **3**, power distributor **134** includes a first electrical contact **138a** coupled to a first electrode assembly **160a** disposed within drill bit **150**, and a second electrical contact **138b** coupled to a second electrode assembly **160b** within drill bit **150**. The electrical contacts **138a**, **138b** are coupled to the electrode assemblies **160a**, **160b** via a pair of communication paths **162**, which may comprise any suitable mechanism or device configured to conduct electrical current therethrough (e.g., such as a wire, cable, conductive trace, etc.). The electrical contacts **138a**, **138b** are circumferentially arranged or spaced about central axis **115**. In some embodiments, the contacts **138a**, **138b** are uniformly-circumferentially spaced about axis **115**. Thus, in the embodiment shown in FIG. **3**, the two electrical contacts **138a**, **138b** are circumferentially spaced about 180° from one another about axis **115** (i.e., electrical contacts **138a**, **138b** radially oppose one another across central axis **115**). However, as will be described in more detail below, the arrangement, number, and spacing of the electrode assemblies **160** on drill bit **150** may be varied in different embodiments.

Referring still to FIGS. **2** and **3**, power distributor **134** also includes a conductive tip **136**. The power distributor **134** is coupled to driveshaft assembly **116** and/or drill bit **150** so that the rotation of driveshaft assembly **116** and drill bit **150** about axis **115** also drives a relative rotation between the tip **136** and the electrical contacts **138a**, **138b**. In particular, in some embodiments, the electrical contacts **138a**, **138b** may rotate about central axis **115** along with drill bit **150** and driveshaft assembly **116**, relative to the conductive tip **136**. The conductive tip **136** may be spaced (e.g., in an axial direction with respect to central axis **115**) from the electrical contacts **138a**, **138b**, and may be energized with electric current from the generator **132**. Thus, during rotation of the drill bit **150** and the relative rotation of the electrical contacts **138a**, **138b**, the tip **136** is progressively brought into close proximity to each of the contacts **138a**, **138b**. When tip **136** is sufficiently close the contacts **138a**, **138b**, electric current “jumps” from the tip **136** to the corresponding electrical contact **138a**, **138b** via an arc **137** (e.g., such as shown between the tip **136** and electrical contact **138a** in FIG. **3**). Thereafter, the electric current flows from the electrical contact to the corresponding electrode assemblies **160a**, **160b** in drill bit **150** via the conductive paths **162**. In some embodiments, the tip **136** may physically engage with contacts **138a**, **138b** so as to conduct electrical current therebetween during drilling operations.

Generally speaking, each electrode assembly **160a**, **160b** includes a pair of outwardly extending electrodes **164** spaced apart from one another. When electric current is conducted to the electrode assemblies **160a**, **160b** via conductive paths **162** (e.g., such as when electric current is conducted from the tip **136** to the corresponding electrical contacts **138a**, **138b** as described above), the electric current may be conducted into at least one of the electrodes **164** whereby it may again “jump” to the other electrode **164** via an arc **166**. Arc **166** may be referred to herein as a plasmatric discharge or plasma that generates increased temperatures and pressures. Thus, the electrode assemblies **160a**, **160b** (as well as electrode assemblies **160** discussed more broadly herein and shown in FIGS. **1**, **2**, and **4-6**) may be referred to herein as “plasma inducing” devices or apparatuses that generate plasma (e.g., arc **166**). During drilling operations, the electrodes **164** may be disposed relatively close to a surface of the formation **7** within borehole **3**, such as, for instance within 1 cm or less, or within 1 mm or less. Large gradients accompanying the formation of plasma **166** may also induce shock waves **168** and cavitation within the fluid disposed in the borehole **3** (e.g., drilling fluid, water, etc.). The induced shockwaves **168** impact formation **7** and thereby form fractures **170** (e.g., cracks, micro-cracks, etc.). In some embodiments, the shockwaves **168** may apply elevated pressures to the formation **7** that are greater than or equal to 1 GPa. As a result, the formation **7** is generally weakened so that drill bit **150** may more easily shear, puncture, etc. the formation **7** and therefore extend borehole **3** during drilling operations.

In some embodiments, the average electrical power for generating plasma **166** between the select pairs of electrodes **164** in electrode assemblies **160a**, **160b** may be less than 20 kW, or may be less than 5 kW (e.g., such as from about 100 W to about 10 kW). Also, the plasma **166** may be generated rapidly between the electrodes **164**, with instantaneous (or near instantaneous) power release of about 10 MW or greater, and may have an energy release of about 10 Joules (J) to about 10 kJ.

In addition, the electrical pulse or current conducted to the electrode assemblies **160a**, **160b** via conductive paths **162**

may be either monopolar or bipolar. In some embodiments, the electrical or current conducted to the electrode assemblies **160a**, **160b** is monopolar and of the electrode **164** of each electrode assembly **160a**, **160b** may receive electric current having a voltage of about 10 kV to about 100 kV. In some embodiments, one of the electrodes **164** of each electrode assembly **160a**, **160b** may be coupled to a ground potential. In some embodiments, the electrical current conducted to electrode assemblies **160a**, **160b** may be bipolar, and one electrode **164** within each electrode assembly **160a**, **160b** may receive a positively biased electric current, while the other electrode **164** of each electrode assembly **160a**, **160b** may receive a negatively biased electric current, wherein the positive and negative biases are made with reference to a ground potential.

In some embodiments, the duration of the plasmatic discharges (e.g., arcs **166**) may occur relatively quickly between electrodes **164**. For instance, in some embodiments, the duration of the plasmatic discharges between electrodes **164** may be 10 nanoseconds (ns) or less, or from about 1 ns to about 1 microsecond (μ s). Additionally, in some embodiments, the plasmatic discharges between electrodes **164** may occur at frequencies of about 1 Hz to about 1 kHz.

In general, drill bit **150** may be any suitable type or design of drill bit for forming borehole **3** in subterranean formation **7**. For instance, drill bit **150** may be a fixed cutter drill bit (e.g., which is sometimes referred to as a “drag bit”) that shears portions of the formation **7** to extend borehole **3**. In some embodiments, drill bit **150** may be a rolling cone drill bit **150** that punctures and crushes the formation **7** to extend borehole **3**. In still other embodiments, drill bit **150** may be another form of drill bit (e.g., including hybrid designs incorporating elements of a fixed cutter and rolling cone drill bit). In the following discussion, a drill bit that may be used as drill bit **150** within BHA **100** according to some embodiments is described in more detail; however, as noted above, it should be appreciated that the drill bit **150** may comprise a number of different designs that may differ from those specifically discussed below.

Referring now to FIGS. 4-6, a drill bit **250** that may be used as drill bit **150** within BHA **100** according to some embodiments is shown. In this embodiment, drill bit **250** includes a so-called fixed cutter drill bit that is configured to shear off portions of a subterranean formation (e.g., formation **7**) to extend a borehole (e.g., borehole **3**) therein.

Generally speaking, drill bit **250** has a central or longitudinal axis **255**, a first or uphole end **250a**, and a second or downhole end **250b**. Central axis **255** of bit **250** is coaxially aligned with central axis **115** of BHA **110** when bit **250** is coupled within BHA **100** as drill bit **150** (see e.g., FIGS. 2 and 4-6). Drill bit **250** is configured to rotate about axis **255** in a cutting direction represented by arrow **206**. In addition, bit **250** includes a bit body **260** extending axially from downhole end **250b**, a threaded connection or pin **270** extending axially from uphole end **250a**, and a shank **280** extending axially between pin **270** and body **260**. Pin **270** couples bit **250** to BHA **100** (see e.g., FIG. 2). Bit body **260**, shank **280**, and pin **270** are coaxially aligned with axis **255**, and thus, each has a central axis coincident with axis **255**.

The portion of bit body **260** that faces the formation at downhole end **250b** includes a bit face **261** provided with a cutting structure **290**. Cutting structure **290** includes a plurality of blades **291**, **292**, **293**, which extend from bit face **291**. In this embodiment, the plurality of blades **291**, **292**, **293** are uniformly circumferentially-spaced on bit face **261** about bit axis **255**.

In this embodiment, blades **291**, **292**, **293** are integrally formed as part of, and extend from, bit body **260** and bit face **261**. In particular, blades **291**, **292**, **293** extend generally radially along bit face **261** and then axially along a portion of the periphery of bit **250**. Blades **291**, **292**, **293** are separated by drilling fluid flow courses or junk slots **294**. Each blade **291**, **292**, **293** has a leading edge or side **291a**, **292a**, **293a**, respectively, and a trailing edge or side **291b**, **292b**, **293b**, respectively, relative to the direction of rotation **206** of bit **250**.

Referring still to FIGS. 4-6, each blade **291**, **292**, **293** includes a cutter-supporting surface **295** for mounting a plurality of cutter elements **300**. In particular, cutter elements **300** are arranged adjacent one another in a radially extending row along the leading edge **291a**, **292a**, **293a** of each blade **291**, **292**, **293**. In this embodiment, each cutter element **300** is a generally cylindrical member that includes a relatively hard material for engaging with and shearing portions of a subterranean formation (e.g., formation **7**) during operations. In some embodiments, the cutter elements **300** may comprise polycrystalline diamond.

Bit body **260** further includes gage pads **297** of substantially equal axial length measured generally parallel to bit axis **255**. Gage pads **297** are circumferentially-spaced about the radially outer surface of bit body **260**. Specifically, one gage pad **297** intersects and extends from each blade **291**, **292**, **293**. In this embodiment, gage pads **297** are integrally formed as part of the bit body **260**. In general, gage pads **297** can help maintain the size of the borehole by a rubbing action when cutter elements **300** wear slightly under gage. Gage pads **297** also help stabilize bit **250** against vibration.

Referring specifically now to FIG. 6, a cross-section of drill bit **250** is shown that shows a profile of with a first blade **291**; however, it should be appreciated that each of the blades **291**, **292**, **293** is generally configured the same, such that the portions and components of the profile of blade **291** are also present along the blades **292**, **293**. In this embodiment, the profile of blades **291**, **292**, **293** (as shown by the representation of the profile of blade **291** in FIG. 6) may generally be divided into three regions conventionally labeled cone region **299a**, shoulder region **299b**, and gage region **299c**. Cone region **299a** includes the radially innermost region of bit body **260**, and extends from bit axis **255** to shoulder region **299b**. In this embodiment, cone region **299a** is generally concave. Adjacent cone region **299a** is the generally convex shoulder region **299b**. The transition between cone region **299a** and shoulder region **299b**, typically referred to as the nose **299d**. Moving radially outward, adjacent shoulder region **299b** is the gage region **299c** which extends substantially parallel to bit axis **105** at the outer radial periphery of composite blade profile **148**. Gage pads **297** define the gage region **299c** and an outer radius of bit body **260**. Cutter elements **300** are provided in cone region **299a**, shoulder region **299b**, and gage region **299c**.

As is also best shown in FIG. 6, bit **250** includes an internal plenum **230** extending axially from uphole end **250a** through pin **270** and shank **280** into bit body **260**. Plenum **230** permits drilling fluid to flow from the tubular string **16** (see e.g., FIGS. 1 and 2) into bit **250**. Flow passages **232** extend from plenum **230** to downhole end **250b**. As best shown in FIGS. 4 and 5, nozzles **234** are seated in the lower end of each flow passage **232**. The nozzles **234** and corresponding flow passages **232** distribute drilling fluid around cutting structure **290** to flush away formation cuttings and to remove heat from cutting structure **290**, and more particularly cutter elements **300**, during drilling.

11

Referring again to FIGS. 4-6, the plurality of electrode assemblies 160 are disposed about the cutting structure 290. As best shown in FIGS. 4 and 5, in this embodiment the electrode assemblies 160 are disposed within the cone region 299a and the shoulder region 299b. In this embodiment, no electrode assemblies 160 are included within the gage region 299c; however, it should be appreciated that in other embodiments, one or more of the electrode assemblies 160 may be included within the gage region 299c. Also, in some embodiments (e.g., such as the embodiment of FIGS. 4-6), the electrode assemblies 160 may be recessed within the cutting structure 290 so as to protect electrodes 164 from impacting the formation (e.g., formation 7) or other components or features during a drilling operation.

In addition, as is best shown in FIG. 5, in this embodiment the electrode assemblies 160 are disposed at different radial positions relative to central axes 115, 225 such that each electrode assembly 160 traces or sweeps through a different orbit 161 about axis 115, 255 as drill bit 150 rotates about axes 115, 255 in the cutting direction 206. In particular, each orbit 161 is radially spaced from the other orbits 161, so that each electrode assembly 160 interacts with a different portion of the formation 7 (see e.g., FIG. 3) during drilling operations. In this embodiment, there are total of four electrode assemblies 160 so that during operations, the electrode assemblies trace four different orbits 161 that are radially spaced moving radially outward from the central axes 115, 255. In some embodiments, the electrode assemblies 160 are arranged so that the orbits 161 are generally uniformly radially spaced; however, in other embodiments, one or more of the orbits 161 traced by the electrode assemblies 160 may not be evenly radially spaced from one another.

Referring now to FIGS. 3 and 6, in some embodiments the conductive paths 162 electrically coupling electrode assemblies 160 to power distribution assembly 132 are routed (e.g., at least partially) through the plenum 230 of drill bit 150. In addition, while not specifically shown, it should be appreciated that conductive paths 162 may also be routed through additional bores or tunnels extending from plenum to electrode assemblies 160. In some embodiments, conductive paths 162 may extend through one or more of the flow passages 232 in addition to the plenum 230. In still other embodiments, conductive paths 162 may extend through tunnels or pathways within drill bit 150 that do not extend through and/or intersect with the plenum 230 or flow passages 232.

Referring now to FIG. 7, an embodiment of a method 400 for drilling a borehole (e.g., such as borehole 3 in FIG. 1) is shown. In describing the features of method 400, reference will be made to the features of system 10 shown in FIGS. 1-3; however, it should be appreciated that method 400 may be performed with other system and assemblies that may be different from those described above for system 10. Thus, reference to system 10 and its components and features (e.g., BHA 100, drill bit 150, drill bit 250, etc.) is merely meant to describe particular embodiments of method 400 and should not be interpreted as limiting all potential embodiments of method 400.

Initially, method 400 begins by rotating a drill bit about a central axis at block 402. For instance, a drill bit (e.g., drill bit 150, 250) may be rotated about a central axis of the drill bit and/or of a bottom hole assembly (e.g., BHA 100, central axis 115). Next, method 400 includes engaging the drill bit with a subterranean formation during the rotating at block 404. In some embodiments, the engaging at block 404 may comprise shearing the formation with a cutting structure of

12

the drill bit (e.g., cutting structure 290 of drill bit 250), and/or puncturing the formation with the drill bit (e.g., such as for a rolling cone drill bit).

Next, method 400 includes generating plasma with a plasma inducing apparatus coupled to the drill bit during the engaging at block 406. For instance, in some embodiments, the plasma inducing apparatus may comprise an electrode assembly (e.g., electrode assembly 160) coupled to the drill bit, and generating plasma at block 406 may comprise flowing electric current to the electrode assembly. In some embodiments, the plasma inducing apparatus (e.g., electrodes 160) may be coupled to a downhole end (e.g., downhole end 250b and cutting structure 290 of drill bit 250) of the drill bit.

Method 400 next includes weakening the subterranean formation with the plasma during the generating at block 408. For instance, in some embodiments weakening the subterranean formation may comprise forming cracks (e.g., cracks 170 in FIG. 3) in the subterranean formation) as a result of the plasma generated at 406. Method 400 also includes extending a borehole within the subterranean formation at block 410. In some embodiments, extending the borehole at 410 may directly result from the rotating, engaging, generating, and weakening of blocks 402, 404, 406, 408, previously described.

The embodiments disclosed herein have included drill bits and associated drilling systems or assemblies (e.g., system 10, BHA 100, drill bit 150) including electrode assemblies (e.g., electrodes 164 within electrode assemblies 160) configured to weaken a subterranean formation that is to be engaged by the drill bit and thereby increase the ROP during a drilling operation. Thus, through use of the embodiments disclosed herein, the time required to drill a borehole may be reduced, so that the costs associated with such a drilling operation may also be reduced.

While the embodiments described herein have included electrode assemblies (e.g., electrode assemblies 160) coupled to a downhole end of a drill bit (e.g., drill bit 150, 250, etc.), it should be appreciated that other embodiments may position electrode assemblies in different locations within system 10 either in lieu of or in addition to the electrode assemblies coupled to the bit as described above. For instance, in some embodiments, system 10 may include a reamer cutter disposed along or uphole of BHA 100 that includes one or more electrode assemblies that may be configured substantially the same as the electrode assemblies 160 described above.

While exemplary embodiments have been shown and described, modifications thereof can be made by one skilled in the art without departing from the scope or teachings herein. The embodiments described herein are exemplary only and are not limiting. Many variations and modifications of the systems, apparatus, and processes described herein are possible and are within the scope of the disclosure. Accordingly, the scope of protection is not limited to the embodiments described herein, but is only limited by the claims that follow, the scope of which shall include all equivalents of the subject matter of the claims. Unless expressly stated otherwise, the steps in a method claim may be performed in any order. The recitation of identifiers such as (a), (b), (c) or (1), (2), (3) before steps in a method claim are not intended to and do not specify a particular order to the steps, but rather are used to simplify subsequent reference to such steps.

What is claimed is:

1. A system for drilling a borehole in a subterranean formation, the system comprising:

13

a tubular string;
 a drill bit coupled to the tubular string and comprising a bit body having a bit face positioned along the bit body;
 a plasma inducing apparatus coupled to the drill bit and comprising an electrode assembly coupled to a downhole end of the drill bit, wherein the electrode assembly comprises one or more pairs of electrodes positioned along the bit face of the drill bit and configured to emit an electrical discharge between the one or more pairs of electrodes to generate plasma for weakening the subterranean formation, the electrical discharge having an average electrical power that is less than 20 kilowatts (kW); and
 a power conversion assembly coupled to the tubular string, wherein the plasma inducing apparatus is configured to generate plasma from electric current generated within the power conversion assembly,
 wherein the drill bit comprises a cutting structure positioned along the bit face and comprising a plurality of cutter elements configured to cut into the subterranean formation as the subterranean formation is weakened by the plasma generated by the electrode assembly.

2. The system of claim 1, wherein the plasma inducing apparatus comprises an electrode assembly coupled to a downhole end of the drill bit, wherein the electrode assembly is configured to emit an electrical discharge to generate plasma.

3. The system of claim 2, comprising:
 a downhole motor coupled to the tubular string, wherein the downhole motor comprises a rotor and a stator; and
 wherein the power conversion assembly is coupled to the rotor of the downhole motor, and
 wherein the power conversion assembly is configured to generate electric current based on a rotation of the rotor within the stator.

4. The system of claim 3, wherein the downhole motor is a positive displacement motor that is configured to rotate the rotor within the stator in response to flowing a fluid between the rotor and the stator.

5. The system of claim 4, wherein the drill bit, the electrode assembly, the downhole motor, and the power conversion assembly are incorporated within a bottom hole assembly that is coupled to the tubular string.

6. The system of claim 5, wherein an instantaneous power release of the electrode assembly is greater than or equal to about 10 MW.

7. The system of claim 1, wherein the plasma inducing apparatus comprises plurality of electrode assemblies coupled to the drill bit, and wherein the power conversion assembly comprises a power distributor that is configured to sequentially provide electric current to the plurality of electrode assemblies.

8. The system of claim 1, wherein the plasma inducing apparatus comprises plurality of electrode assemblies coupled to the drill bit, wherein the electrode assemblies are configured to trace a plurality of radially spaced orbits about a central axis of the drill bit when the drill bit is rotated about the central axis.

9. A system for drilling a borehole in a subterranean formation, the system comprising:
 a tubular string;
 a bottom hole assembly coupled to the tubular string, the bottom hole assembly comprising:
 a downhole motor comprising a stator and a rotor;
 a power conversion assembly configured to generate electric current from operation of the downhole motor;

14

a drill bit having a central axis and comprising a bit body having a bit face positioned along the bit body, wherein the drill bit is rotatable about the central axis in response to relative rotation between the rotor and the stator of the downhole motor; and
 an electrode assembly coupled to a downhole end of the drill bit, wherein the electrode assembly is configured to generate plasma when energized with electric current from the power conversion assembly;
 wherein the drill bit comprises a cutting structure positioned along the bit face and comprising a plurality of cutter elements configured to cut into the subterranean formation as the subterranean formation is weakened by the plasma generated by the electrode assembly.

10. The system of claim 9, comprising a plurality of electrode assemblies coupled to the downhole end of the drill bit,
 wherein the drill bit comprises a fixed cutter drill bit, and
 wherein the plurality of electrode assemblies are disposed within a cone region and shoulder region of the fixed cutter drill bit.

11. The system of claim 10, wherein the plurality of electrode assemblies are configured to trace a plurality of radially spaced orbits about a central axis of the drill bit when the drill bit is rotated about the central axis.

12. The system of claim 11, wherein the downhole motor is configured to drive rotation of the drill bit about the central axis.

13. The system of claim 9, wherein the power conversion assembly comprises:
 an alternator coupled to the rotor of the downhole motor, and configured to generate an electric current as a result of rotation of the rotor;
 a power storage assembly that is configured to store electrical power generated by the alternator; and
 a transformer electrically coupled to the power storage assembly and configured to increase a voltage of electric current.

14. The system of claim 13, wherein the power conversion assembly comprises a voltage multiplier electrically coupled between the transformer and the electrode assembly.

15. The system of claim 14, wherein the voltage multiplier comprises a Cockcroft-Walton generator.

16. A method of drilling a borehole in a subterranean formation, the method comprising:
 (a) rotating a drill bit about a central axis, the drill bit comprising a bit body having a bit face positioned along the bit body;
 (b) engaging the drill bit with the subterranean formation during (a);
 (c) generating electric current downhole;
 (d) emitting an electrical discharge between one or more pairs of electrodes of an electrode assembly positioned along the bit face of the drill bit to generate plasma during (b) using the electric current generated in (c), wherein the electrical discharge generated between the one or more pairs of electrodes has an average electrical power that is less than 20 kilowatts (KW);
 (e) weakening the subterranean formation with the plasma during (d); and
 (f) cutting into the weakened subterranean formation with a plurality of cutting elements of a cutting structure positioned along the bit face to extend the borehole within a subterranean formation as a result of (a)-(e).

17. The method of claim 16, wherein (d) comprises forming one or more cracks in the subterranean formation.

15

18. The method of claim **17**, wherein the plasma inducing apparatus comprises an electrode assembly, and wherein (d) comprises flowing the electric current generated in (c) to the electrode assembly.

19. The method of claim **18**, wherein (d) comprises 5 rotating a rotor of a downhole motor.

20. The method of claim **17**, wherein (c) comprises sequentially generating plasma at a plurality of electrode assemblies coupled to the drill bit by sequentially energizing the plurality of electrode assemblies with a power distribu- 10 tor.

* * * * *

16